



System	
Compression	Standard H.265
Operating System	Embedded LINUX
Video	
Network Access Bandwidth	32Mbps
Input Resolution	5MP, 4MP, 3MP, 1080P, 960P, 720P real time
Network Access	4 CH IPC input
Output	HDMI×1:1920×1080/1280×1024/1024×768 VGA×1:1920×1080/1280×1024/1024×768
Audio	
Input	4 CH IPC audio input
2-way Audio	No
Local Output	No (HDMI supports the audio output)
Record	
Resolution	5MP, 4MP, 3MP, 1080P, 960P, 720P
Frame Rate	25fps/30fps(PAL/NTSC)
Bite Stream	32Kbps-8Mbps
Image Quality	5 Level
Playback	
Simultaneous Playback	Max 4 CH
Network	
Interface	RJ45 10/100Mbps × 1
Network Protocol	TCP/IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP, ONVIF, GB28181
Storage	
HDD	SATA×1
Max Capacity for 1 single HDD	6T

Backup	
USB Backup	Yes
eSata Backup	No
Interface	
Alarm In	No
Alarm Output	No
Communication	No
Remote	Optional
USB	USB2.0×2 (rear panel)
Others	
Case	Mini 1U
Dimensions(mm)	255×233×42(W×D×H)
Power Supply	DC12V
Consumption	≤ 6W (without HDD)
Work Environment	-10 ~ 50 °C, 10% ~ 90% humidity