

RTX3

Wireless Expansion Module

Features

- 32 wireless addressable zones
- Maximum number of remote controls: 999 with EVO Series, 32 with Spectra SP Series
- Supports wireless PGMs (8 with EVO Series, 16 with Spectra SP Series only)
- Supports SR130 and SR150 Wireless Sirens
- Supports all Magellan transmitters including 2WPGM
- Supports 2 RPT1 and 8 K37 (Spectra SP Series only)



Technical Specifications

Power input voltage	12Vdc
Frequency	433MHz or 868MHz
Sensitivity	-120 dBm
Current consumption	50 mA
Dimensions and Weight	15cm x 16cm x 3cm (6in x 6.5in x 1.1in) / 24g
Operating temperature	0°C to 49°C (32°F to 120°F)
Humidity	5 - 90%
PGM outputs	PGM1 and PGM2 - 150mA PGM transistor outputs PGM3 - form C relay output rated at 5A/28Vdc, N.O./N.C. (PGM4 optional)
Range	Refer to the appropriate transmitter <i>Instructions</i>
Other	Di-pole antenna; Error Correction Algorithm
Approvals	EN50131-3: Security Grade 2, Environmental Class II, Certification Body Intertek. For the latest information on product approvals, visit our website at paradox.com .