

SR130

Wireless Outdoor Siren with Built-in Strobe Light

Features

- Battery operated (3 "C" alkaline batteries) Weather-resistant design with UV protection
- 2-way, fully supervised communication with the control panel
- 100dB Piezo siren
- Separate alarm notifications for intrusion and fire
- Dual-tamper detection (cover and wall)
- Squawk functionality
- Wireless range in a typical residential environment: Up to 70m (230 ft)
- Fully powered using three 1.5 Vdc type "C" alkaline batteries (included)
- Signal strength/RF transmission and status LED
- Operating temperature: -25°C to 55°C (-13°F to 131°F)
- RF frequency: 433MHz or 868MHz
- Dimensions: 13.4cm x 21.17cm x 5.1cm (5.29in x 8.34in x 2.01 in)
- Compatible with MG5000 and MG5050 V4.0 or higher, MG5075, Spectra SP series V4.0 or higher (except SP4000) when using an RTX3 V1.5 or higher, as well as with MG6250 V3.0 and higher



Technical Specifications

Specification	Description
Power Supply	3x 1.5 VDC "C" alkaline batteries.
Battery life	Up to 3 years based on normal use (e.g., 2 alarms per year with strobe for 2.5 hours and 8 squawks per day at an average of 25°C (77°F) with default alarm time set to 4 minutes. If the alarm is set for more than 4 minutes, the battery life may be reduced).
Current Consumption	Standby: 5.75 µA, Maximum: 450 mA
Battery Low Voltage Signal	Signal sent at 4.1 VDC
RF frequency	433 MHz or 868 MHz
RF range	Up to 70m (230 ft)
Siren	100 dBA or more (1 meter) Acoustic output type: Tone
Humidity Range	5% to 90%
Dimensions	13.43 x 21.17 x 5.1 cm (5.29 x 8.34 x 2.01 in)
Weight	365g /12.87 oz., 567g/20 oz. with batteries