



System	
Main Processor	HI3521D
Operating System	Embedded LINUX
Video	
Input	<b>Analog:</b> 4*(TVI/AHD: 8MP; TVI/AHD: 5MP; AHD/TVI/CVI: 4MP; AHD/TVI: 3MP; AHD/TVI/CVI: 1080P/720P; Analog: 960H) <b>Analog+Network:</b> 2*Analog+7*network(Max 8MP) <b>Network:</b> 16*network(Max 8MP)(Total incoming bandwidth ≤80M)
Input	4CH BNC
Signal Type	Analog/AHD/CVI/TVI 2.0/TVI 3.0/Network
Output	1HD,1 VGA
Audio	
Input	4 Channel, RCA
Two-way Audio	NO
Output	1 Channel, RCA
Alarm	
Sensor Input	NO
Output	NO
Motion Detection	4 Channel (max 16 Channel in pure network mode)
Trigger Events	Recording, Email, Screen tips, Buzzer, Push notifications (motion detection)
Email Alarm	Send Image to The Designated E-mail
PTZ	
Interface	RS485
Protocol	Pelco-D, Pelco-P
Baud Rate	110~921600
Address	0~255
Display	
VGA	<b>Resolution:</b> 1920 × 1080P/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
HD Output	<b>Resolution:</b> 3840×2160/30Hz, 2560×1440/30Hz, 1920 × 1080P/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Display Split	16 Channel/9 Channel/4 Channel / 1Channel
Privacy Masking	3 Rectangular Zones (Each camera)
OSD	Camera title, Time, Video loss, Alarm, Motion detection, Recording
Certificate	
Certificate	CE, FCC, RoHS

Recording	
Video Compression	H.265/H.265+/H.264/H.264+
Audio Compression	G.711u
Resolution	8MP(3840×2160), 5MP(2592×1944),4MP(2560×1440),3MP(2048×1536),1080P(1920×1080),720P(1280×720),960H(P:960×576/N:960×480)
Video Quality	worst/worse/ordinary/well/best
Record Rate	<b>Analog:</b> <b>PAL:</b> 8MP(3840*2160 8*8fps), 5MP(2592×1944 4*12fps), 4MP(2560×1440 4*15fps),3MP(2048×1536 4*18fps);1080P(1920x1080 4*25fps),720P(1280×720 4*25fps), 960H(960×576 4*25fps) <b>NTSC:</b> 8MP(3840*2160 8*8fps), PAL:5MP(2592×1944 4*12fps), 4MP(2560×1440 4*15fps),3MP(2048×1536 4*18fps),1080P(1920x1080 4*30fps),720P(1280×720 4*30fps), 960H(960×480 4*30fps) <b>Pure IP(H.265+):</b> <b>PAL:</b> 4k@8x25fps, 5MP@12x25fps,4MP@16x25fps, 3MP@16x25fps, 1080P@16x25fps, 960P@16x25fps, 720P@16x25fps, D1@16x25fps <b>NTSC:</b> 4k@8x30fps, 5MP@12x30fps,4MP@16x30fps, 3MP@16x30fps, 1080P@16x30fps, 960P@16x30fps, 720P@16x30fps, D1@16x30fps
Record Mode	Manual\Timer\Motion Detection
Playback & Backup	
Decode Capability	2CH 1080P@30fps
Sync Playback	<b>Pure Analog:</b> 4CH 8M@8fps, 4CH 5M@12fps, 4CH 4M@15fps, 4CH 3M@18fps, 4CH 1080p@30fps <b>Mix Mode:</b> 4CH 1080P@30fps, 3CH 3MP@18fps, 2CH 5M@12fps, ,1CH 5MP@30fps, 1CH 4K@30fps <b>Pure IPC:</b> 1CH 4K@30fps, 2CH 5MP@30fps, 3CH 4MP@30fps, 4CH 3M@30fps, 4CH 1080P@30fps, 4CH 960P@30fps, 4CH 720P@30fps
Remote Playback	4 Channel / 1Channel
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Fast play, Rewind, Digital Zoom, Full screen
Smart Phone Playback	4 Channel
Backup Mode	USB Device (with format FAT 32 ) / Network
Network	
Interface	1 RJ45 10M/100M Adaptive Ethernet Interface
Network Functions	TCP/IP, HTTP, UPnP, DNS, NTP, SMTP, PPPoE, DHCP, FTP, DDNS, RTP, RTSP, RTCP
DDNS	Dyndns, changeip, no-ip, Oray, A-PRESS, MYQSEE, SKDDNS, SMART-EYES, ZEBEYE
Web Browser	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53)
CMS Software Support	Windows 7 / Windows 8 / Windows 10
Extra Stream	D1/CIF (1~30fps)
Smart Phone	iPhone, ipad, Android ,Android pad
Hard Disk Driver	
Interface Type	1 SATA Interface
Capacity	1 SATA Hard Disk (2.5"/3.5" SATA, Up to 6TB)
General	
Language	Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Farisa, German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, korean, Dutch, Greek
UTC Control	YES
USB Interface	2 USB 2.0 Interfaces
Power consumption	DC 12V ≤6W (Without Hard Disk)
Working Environment	-10~55°C/10~90%
Dimension	(W×D×H) 260*215*43(mm)
Weight	2.0kg (Without HDD)